

# GDHF

150NPT-25G-1M-SAEJ1488

- Diesel fuel coalescing filter for dispensing or polishing filtration applications up to 25 GPM
- All-aluminum filter housing is fully compatible with diesel and biodiesel blends
- Uses Proprietary **GeoDry** element technology which exceed SAEJ1488 requirements

**GeoDry**



## Filter Assembly #7645495

Flow Rating:	Up to 25 gpm
Max. Operating Pressure:	150 psi
Min. Yield:	1189 psi
Temp. Range:	32° to 225°F (No Heater)
Bypass Setting:	40 psi
Head/Port:	Cast Aluminum
Element Case:	Anodized Aluminum
Sump:	Anodized Aluminum
Element Change Clearance:	4.5" Min.

Filter Assembly #7645495  
GDHF-150NPT-25G-1M-SAEJ1488

SAP #7645509  
Spare Element - GDF-25G-1M-SAEJ1488

## SAE J1488 - Emulsified Water/Fuel Separation Summary

	5 GPM	10 GPM	15 GPM
Sample ID#	Avg. Efficiency (3 Runs)	Avg. Efficiency (3 Runs)	Avg. Efficiency (3 Runs)
1	99.24%	98.34%	95.72%
2	99.20%	97.99%	96.48%
3	99.05%	98.10%	96.72%
Std. Dev.:	0.10%	0.18%	0.53%
Average:	99.16%	98.14%	96.31%

