

PC3-PFHF

PC3-PFHF-70G-3M-3PH-230

- Diesel fuel cart with bag housing pre-filter (for removal of microbial bloom contamination and rust), particulate filter, and high efficiency coalescing filter (for single pass removal of emulsified and free-water), and pump motor combo 70 GPM (230V/460V - 3 Phase)
- Perfect for kidney loop polishing or single pass transfer or diesel fuel in larger storage tanks
- Aluminum filter housings are fully compatible with diesel and biodiesel blends
- Uses Proprietary **GeoDry** and **PureFuel** element technology which exceed SAEJ1488 requirements



Bulk Diesel Cart #7645504

Flow Rating:	70 gpm
Temp. Range:	32° to 150°F (No Heater)
Bypass Indication PFHF:	15 psi
GDHF Bypass Indication/ Cracking:	25 psi/30 psi
PFHF Bypass Indication/ Cracking:	15 psi/20 psi
Porting Base:	Anodized Aluminum
Pre-Filter Bag Housing:	304 Stainless
GDHF & PFHF	Aluminum w/ Epoxy Paint Electroless Nickel Plating
PFHF Element Change Clearance:	36" Min.
GDHF Element Change Clearance:	34" Min.
Full Load Motor Amps:	13.0A @ 230V, 6.5A @ 460V
Motor Voltage (Frequency):	1230/460 VAC (60HZ) - 3 Phase
Service Factor Amp:	1.15 SF at 40°C (104° F) / 1.0 SF at 65° C (149° F)

PureFuels Spare Element #7645513
PF-70G-3M

PureFuels Spare Bags #7631446
PEF25P2PH - 25µ Polyfelt media
(Sold in Qty 50 Only)

GeoDry Spare Element #7645514
GDF-70G-1M

