

Cleaning The Environment One Drop at A Time

Fuel Polishing Rolling Cart Assemblies

PureFuels FPS-C2 (14 & 25) Models

Specifically designed for Portable Use with multiple Bulk Diesel storage tanks. The Rolling Fuel Cart moves from tank to tank and polish the fuel h the same way a permanently installed fuel polishing system does but with the flexibility of moving from tank to tank. It's perfect for contractors and owners of multiple storage tanks. Specifically Designed for High-Flow Bulk Tank Kidney Loop / Recirculation.

GeoDry coalescor and PureFuels particulate filters achieves and succeed the diesel generator's fuel injector OEMs standard of ISO 4406:1999 of 12/9/6. PureFuels removes 50% more contaminants with results to 11/9/6. *GeoDry* coalescor removes free and emulsified water to SAE J1488_2010 Standards for critical mission applications for hospitals and life support systems.

- GeoDry SAE J1488_2010 certified coalescing
- 3 µm Particulate for ISO:1999 12/9/6
- Bulk Diesel Fuel Cart
- Visual Pop-Up with Manual Reset
- 25 Gpm Suction Stinging with Supply and Return Hoses.
- Positive Displacement Pumps
- Off/On Power Switch

Dimensions: 28W X 41H

Flow Rates: 14 & 25 Gpm.

Psi: 100 Psi Standard with Other Options Available

Inlet / Outlet Piping: 1" / 1-1/2"

Power: Single Phase 115 60hz. 6' Power Cord.

Pumps: Positive Displacement



FPS-C2-GD-14G-1M-1488-1PH115V MODEL

Stages: Standard (Stage-1, 4 Micron), (Stage-2, 1 Micron Iso 12/9/6), (Stage-3 Water Removal).

Standard: Differential Pressure Sensor and Sight Glass on Both Filter Housings

Rating: Pump TEFC Rated for Outdoor Use.

Application: Bulk Diesel Fuel Cart. Move from tank to tank and polish the fuel. It's perfect for contractors and owners of multiple tanks.